

RFID-reader



Proximity reader for connection to the SESAM analysis and control units. With an integrated dual-LED (green/red) for optical signaling and a Piezo-buzzer for acoustic signaling. All colors and the Piezo-buzzer can be addressed freely.

Also available with Wiegand interface!

technical data:

- » transponder/card: EM4102
 - » Wall mounted, flush mounting kit 1 optional
 - » Reading distance approx. 2 cm
 - » Connection cable 4 m
 - » Environmental protection class IV (for outdoor areas)
 - » **VdS-C, approval number, refer to the controller** (without keyboard reader up to class B)
 - » power consumption refer to the table on page 44
- Dimensions LxWxH: 80x50x25 mm



article description	item-no.
aluminum powder coated white	HFS-LWA-APW
aluminum powder coated silver	HFS-LWA-APS
aluminum anodized silver	HFS-LWA-AES
RAL or respectively special colors are available upon request	HFS-LWA-RAL

RFID-reader with keypad



Proximity reader with keypad for connection to the SESAM analysis and control units. With an integrated dual-LED (green/red) for optical signaling and a Piezo-buzzer for acoustic signaling. All colors and the Piezo-buzzer can be addressed freely.

Also available with Wiegand interface!

technical data:

- » transponder/card: EM4102
 - » Wall mounted, flush mounting kit 3 optional
 - » stable stainless steel keyboard
 - » Reading distance approx. 2 cm
 - » Connection cable 4 m
 - » Environmental protection class IV (for outdoor areas)
 - » **VdS-C, approval number, refer to controller**
 - » power consumption refer to the table on page 44
- Dimensions LxWxH: 160x50x25 mm



article description	item-no.
aluminum powder coated white	HFS-TKWA-APW
aluminum powder coated silver	HFS-TKWA-APS
aluminum anodized silver	HFS-TKWA-AES
RAL or respectively special colors are available upon request	HFS-TKWA-RAL