

Mifare-reader

Mifare proximity reader for connection to the SESAM analysis and control units. With an integrated dual-LED (green/red) for optical signaling and a Piezo-buzzer for acoustic signaling. All colors and the Piezo-buzzer can be addressed freely.

Also available with Wiegand interface!

technical data:

- » Mifare classic, ultralight, ultralight C, light, mini, Standard 1k, Standard 4k, DESFire
- » Wall mounted, flush mounting kit 1 optional
- » Reading distance approx. 2,5 cm
- » Connection cable 4 m
- » Environmental protection class IV (for outdoor areas)
Dimensions LxWxH: 80x50x25 mm
- » power consumption refer to the table on page 44



article description	item-no.
aluminum powder coated white	HMS-LWA-APW
aluminum powder coated silver	HMS-LWA-APS
aluminum anodized silver	HMS-LWA-AES
RAL or respectively special colors are available upon request	HMS-LWA-RAL

Mifare-reader with keypad

Mifare proximity reader with keypad for connection to the SESAM analysis and control units. With an integrated dual-LED (green/red) for optical signaling and a Piezo-buzzer for acoustic signaling. All colors and the Piezo-buzzer can be addressed freely.

Also available with Wiegand interface!

technical data:

- » Mifare classic, ultralight, ultralight C, light, mini, Standard 1k, Standard 4k, DESFire
- » Wall mounted, flush mounting kit 3 optional
- » Reading distance approx. 2,5 cm
- » Connection cable 4 m
- » Environmental protection class IV (for outdoor areas)
Dimensions LxWxH: 80x50x25 mm
- » power consumption refer to the table on page 44



article description	item-no.
aluminum powder coated white	HMS-TKWA-APW
aluminum powder coated silver	HMS-TKWA-APS
aluminum anodized silver	HMS-TKWA-AES
RAL or respectively special colors are available upon request	HMS-TKWA-RAL